Testing the best method to prepare recent and fossil brachiopod shells for SEM analysis

Crippa G. & Ye F.


After the treatment sections were rinsed with distilled water.



The analysis of shell and skeleton microstructures by Scanning Electron Microscope (SEM) is a fundamental step in the study of the mineralised parts of marine and terrestrial organisms and it provides invaluable information in different fields of palaeontology, from the comprehension of evolutionary taxonomy and of biomineralisation processes to


n precipitating their low-magnesium calcite shells in isotopic equilibrium with ambient seawater, brachiopods are excellent archives of past seawater temperature and ocean hemistry. However, diagenetic processes may alter the original microstructure (in the form of recrystallisation, amalgamation and/or dissolution of the fabric) and reochemical composition: the SEM analysis of the microstructure represents one of the most common method used to test fossil shell preservation and eventually exclude iagenetic alteration. Notwithstanding the importance of this analysis, only few, scattered data have been published about the preparation and cleaning of brachiopod shells or SEM analyses. Here, we aim to identify a general protocol for the preparation of recent and fossil brachiopod shells for the study at the SEM, besides checking the esponse of the shell mineral fabric to: a) the resin used to embed the valves before cutting and b) different times of exposure to hydrochloric acid (HCl), hydrogen peroxide H₂O₂) and bleach (Crippa et al., 2016).

Recent taxa analysed include Liothyrella uva (Broderip, 1833) (LU) and Liothyrella neozelanica (Thomson, 1918) (LN), respectively collected from Antarctica and New Zealand; fossil shells belong to Terebratula scillae (Seguenza, 1871) coming from the lower Pleistocene Stirone River sedimentary succession in Northern Italy. Terebratulid brachiopods have usually a two- or three layered mineralised shell (primary, secondary and tertiary layers). The secondary layer has a higher organic content compared to the primary and tertiary ones. The removal of the organic matrix (OM) is essential to obtain clear and distinct images of the mineralised shell fabric of recent brachiopods at the SEM. The problem does not arise in the case of fossil shells, as OM is generally




Resin: embedding vs not embedding


In valve sections not treated with H₂O₂ or bleach, the OM is abundan and forms coverages and/or filaments which do not allow to clearly distinguish the fabric. These coverages/filaments occur both in the specimens embedded in avaldite and in the ones without the resin



Shells treated with bleach or H₂O₂ appear cleaner due to the effect o the chemical solution which dissolve the OM. No difference observed between specimens embedded or not embedded in the resin and experimenting the same procedure.




In order to remove OM two procedures have been used: 1) immersion in diluted commercial bleach (5% v/v) for two hours and one day; 2) immersion in hydrogen peroxide (H.O.) with different concentrations for different time intervals; a) 36 volume (11%) H₂O₂ for two hours and for one day; b) 12 volume (3.6%) H₂O₂ for one day and for three days,



Rleach for 2 hours: the shells exhibit filaments of OM around the fihers

Bleach for 2 hours: the shells are not clean from the OM. Note that the OM is more evident around fibers transversal section than oblique/parallel ones






present around the fibers of the secondary layer

36 volume (11%) H₂O₂ for 2 hours the content in OM decreases due to the H₂O₂ treatment, but the shell is

6 volume (11%) H₂O₂ for 1 day; OM is dissolved; however, a slight dissolution appears on the fiber surface



12 volume (3.6%) H₂O₂ for 3 days; OM is dissolved, but a slight dissolution is present on the fiber surface

12 volume (3.6%) H₂O₂ for 3 days; the surface of each fiber is dissolved in correspondence of the ttachment sites of the OM

36 volume (11%) H₂O₂ for 1 day: the crystallites and prisms of the primary and tertiary lavers are not affected by H₂O₂ dissolution




To better understand the effect of HCl on brachionod shells, valve sections are immersed in the acid for different times (0, 3, 15 and 30 seconds)



No HCI treatment: Silicon Carbide (SiC) residues remain on the valve surface masking the fahric



s clean from SiC residues and ne fabric is distinct: the OM is clearly visible around the fibers




HCl for 15 seconds, corrosion annears on the surface of the

HCl for 30 seconds the fibers are corroded; note the sheaths of OM around the fibers

Freell challe

Fossil shell sections are not treated with diluted bleach or H₂O₂ as their shell usually do not contain OM. We therefore check the degree of penetration of the araldite resin into the shell substance from the section. The scheduled time of shell etching (15 seconds) does not cause damage or corrosion of the fabric.





Fossil shells not embedded in resin show no filaments or coverages of OM around and above the fibers of the secondary layer, besides isplaying void punctae



In fossil shells embedded, the resin penetrates only inside the void punctae, but not within the empty spaces left by the decomposition of OM around the fibers



disturbed surface layer - due to SiC residues but also to highlight the details of the fabric. Time of etching: 3 seconds for recent shells, 15 seconds for fossil ones. After etching, immediately rinse the shells with abundant

the SEM. Rinse with distilled water

Which is the best method to reveal the details of the shell fabric?





Only for recent specimens. Best treatment: bleach for 1 day, 36 volume H₂O₂ for 1 day or 12 volume H₂O₂ for 3 days. Although this causes a slight dissolution of the fiber surfaces, this does not compromise the morphology of the fabric and the analysis at

5% HCl etching Essential sten to remove the mechanically water to stop the effect of the acid



Resin embedding and cuttin Resin: araldite DER + hardener HY956 (10:1

or 8:2). Give strength to valves to avoid shell breakage during cutting with a low speed saw with a thin diamond blade



2 Smoothing This step has to be done employing Silicon Carbide (SiC) with two different granulometries: first, the coarser one (400) to remove the scratches left on the shell surface by the blade during the cutting, then the finer one (1000) to complete the smoothing. Rinse with distilled water to remove SiC residues



Some final considerations...

Coverages and filaments of OM are more evident in the fibrous secondary layer, particularly when fibers appear in cross sections; in the primary and tertiary layers, OM was not detected at this scale of

Chemicals cause a slight dissolution of the surface of the secondary fibers; in contrast, the crystallites and prisms of the primary and tertiary layers do not exhibit dissolution

In testing the different procedures used to remove OM shell sections of L. uva seem more difficult to clean than the ones belonging to L.

These observations can be explained with the different content in OM of the fabric of the three shell layers. The secondary layer has a high OM content, both intercrystalline and intracrystalline (e.g., Gaspard, 2007; Pérez-Huerta et al., 2009). The primary and tertiary layers have, instead, a lower OM content: in fact, they do not exude organic sheets between primary crystallites or tertiary prisms (Williams et al., 1997; Schmahl et al., 2012). In having a higher organic content, coverages and filaments of OM are more developed in the secondary layer. If not fixed with organic compound, as glutaraldehyde (Gaspard et al., 2007; Immel et al., 2015; Casella et al., 2017), or dissolved with appropriate chemical solutions, OM represents an obstacle to examine shell microstructures at the SEM.

Fibers cut in transverse section show a preferential orientation which allow to better expose the organic membranes which surround each fibers: this does not occur in fibers with parallel or oblique orientation.

Chemicals intercrystalline OM, leave a depression in correspondence of the attachment sites of the organic membranes on the surface of the fibers, producing dissolution.

L. uva has only a primary and a dissolving secondary layer, whereas L. neozelanica has a primary, a secondary and also a tertiary layer (Peck et al., 1997). The higher OM content of the shell of L. uva (Watson et al., 2012) results in a greater difficulty to clean it

Casella L. et al. (2017). Experimental diagenesis: insights into aragonite to Peck S.L. et al. (1997). Growth and metabolism in the Antarctic brachiop alcite transformation of Arctica islandica shells by hydrothermal treatment.

Waston S. et al. (2012). Marine invertebrate Gaspard D. et al. (2007). Been tractices of fleeten thyrochonelliform proposits: microstructure and carbonate saturation: implications in substance of the control of the dependence of the control of th

Immel F. et al. (2015). Shell proteome of rhynchonelliform brachlopods. Journal Calcified Tissue Research, 6: 11-19.

Liothyrella uva. Philosophical Transactions of the Royal Society B: Biological, 352: 851-858 Crippa G. et al. (2016). Which is the best method to prepare invertebrate shells percet-fluerta. A. et al. (2009). Brachlopod punctae: A complexity in shell

for SRA analysis? Testing different techniques on recent and fossil brachiopods-biomineralisation. *Journal of Structural Biology*, 167: 62-67.
Watson S, et al. (2012). Marine invertebrale saletion size varies with latitude, Gapard D, et al. (2007). Shell matrices of Recent rhynchonelliform emperature and carbonate sizuration: implications for global change and ocean emperature and carbonate sizuration: implications for global change and ocean

Williams A. (1970). Spiral growth of the laminar shell of the brachiopod Crania.

This project was in part funded from the European Union's Horizon 2020 research and innovation programme under grant agreement No 643084.